

NOTES:UNLESSOTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

LMA-5023


600 – 630 MHz 有源三倍频器 Active Frequency Tripler

—电气技术参数 Electrical Specifications—


输入频率范围 Input Frequency Range:	600 – 630MHz
输出频率范围 Output Frequency Range:	1800 – 1890MHz
输入功率 Input Power:	0dBm
输出功率 Input Power:	+12dBm
谐波抑制 F0 Harmonic Suppression F0:	35dB
输入驻波比 Input VSWR:	1.7:1
输出驻波比 Output VSWR:	2.1:1
直流偏置电压 DC Power Supply:	12V
直流偏置电流 DC Current Supply:	160mA
工作温度 Operation Temperature:	-40 ~ +85°C
存储温度 Storage Temperature:	-55 ~ +105°C

—机械技术参数 Mechanical Specifications—

输入连接器 Input Interface:	SMA-F
输出连接器 Output Interface:	SMA-F
尺寸 Size (excluding connectors):	/
重量 Weight:	/



	A	B	C	D	E	F	G	H	I	J
Inch	1.250	1.250	0.563	0.450	1.000	0.625	1.000	0.250	0.500	0.187
mm	31.75	31.75	14.29	11.43	25.40	15.88	25.40	6.35	12.70	4.76

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .X±0.1 ±1° ±2/5 .XX±0.03 .XXX±0.012						P/N: LMA-5023	
		Approvals	DATE	www.lairmw.com sales@lairmw.com			
HOLE DIAMETER .35 TO 3.20 3.21 TO 6.35 6.36 TO 12.70 12.71 TO 19.05 19.06 TO 25.40 25.41 TO 50.80	TOLERANCES +.05/- .02 +.10/- .03 +.15/- .03 +.20/- .03 +.25/- .03 +.30/- .03	DRWN	600 – 630 MHz				
		ENG	Active Frequency Tripler				
		CHK	SIZE	CAGE NO	DWG NO.	REV	
		Q.A.	A3			1	
			SCALE	UNIT	SHEET 1 OF 1		
			3:2	mm			