

Satellite Communication Series SSPA 卫星通信 SSPA 系列
V Band 200W GaN SSPA V 波段 200W GaN 固态功率放大器

产品特性 Product Features

- 工作频率范围 Frequency Coverage: 47.2 – 51.4GHz
- 输出功率范围 Output Power Range: $\geq 200\text{W}$
- 基于氮化镓的极高线性度及高能效 Extreme GaN Linearity and Efficiency
- 稳定性高、可靠性高、寿命长 High Stability, High Reliability, and Long Life

电气特性 Electrical Characteristics

工作频率 Operating Frequency	47.2-51.4GHz(Standard), 47.2-52.4GHz(Extended)
饱和输出功率 Output Power (Psat)	$\geq 200\text{W}$
线性输出功率 Output Power(Plinear)	$\geq 100\text{W}$
增益 Gain	$\geq 60\text{dB}$
增益变化 Gain Variation	1.5dB p-p@250MHz; 2.5dB p-p@1GHz; 4dB p-p@4.2GHz
增益稳定度 Gain Stability	$\leq \pm 0.25\text{dB}/24\text{h}$ @constant temperature & drive level
增益调节范围 Gain Adjustment Range	25dB, 0.1dB step
杂散 Spurious	$\leq -60\text{dBc}$
谐波 Harmonic	$\leq -60\text{dBc}$ (Option: filter)
输入驻波 Input VSWR	$\leq 1.8:1$
三阶互调 Third Order IMD	$\leq -25\text{dBc}$ @3dB back-off from Psat, 2 equal carriers 5MHz apart
邻信道功率比 ACPR	$\leq -25\text{dBc}$ @Plinear
调幅调相变换 AM/PM Conversion	2°/dB max.(@Plinear)
群时延 Group Delay (40MHz)	0.02ns/MHz Linear; 1ns p-p max.
噪声功率密度 Noise Power Density	$\leq -150\text{dBW}/4\text{kHz}$ @Receive Band $\leq -70\text{dBW}/4\text{kHz}$ @Trasmit Band
相位噪声 Phase Noise	$\leq -63\text{dBc}/\text{Hz}$ @100Hz;
	$\leq -73\text{dBc}/\text{Hz}$ @1kHz;
	$\leq -83\text{dBc}/\text{Hz}$ @10KHz;
	$\leq -93\text{dBc}/\text{Hz}$ @100KHz;
供电 Supply Power	220VAC($\pm 20\%$); 47~63Hz
功耗 Power Consumption	$\leq 2.8\text{KW}$

Satellite Communication Series SSPA 卫星通信 SSPA 系列
V Band 200W GaN SSPA V 波段 200W GaN 固态功率放大器**机械特性 Mechanical Characteristics**

射频输入/出接口 RF I/O Interface	WR19/WR19
射频采样接口 RF Sampling Interface	2.4-Female
供电接口 Power Supply Interface	航空插座 Aviation Socket
M&C 接口 M&C Interface	MS3112E14-19S(Ethernet or RS422/RS485/RS232)
外形尺寸 Dimension(LxWxH)	420*270*220mm
重量 Weight	25Kg

环境特性 Environmental Characteristics

工作温度 Operating Temperature	-40~+55°C
贮存温度 Storage Temperature	-50~+80°C
湿度 Humidity	100%, Condensing
高度 Altitude	10,000' AMSL, de-rated 2°C/1,000 from AMSL

监控功能 Monitor & Control Functions

监控 Monitor	输出功率、反射功率、模块温度、模块电流等 Output Power、Reflect Power、Module Temperature、Module Current, etc.
控制 Control	电源开/关、射频开/关、上行功率控制、增益调节等 Power On/Off、RF On/Off、Uplink Power Control、Gain Adjustment, etc.
保护 Protection	过温保护、过流保护、过反射保护 Over Temperature Protection、Over Current Protection、Over Reflection Protection